



Day 21, Today's Topic

# Default Function Arguments

DAILY  
JS



```
/* ===== */
/* ===== Daily JS - Day 21 ===== */
/* ===== */
```

## # Default Function Arguments

If you come from another language, you must be aware of this feature called "Default Params" or "Default Function Arguments".

The idea is very simple, in case there is no value or undefined passed in the functional argument, we already take care of this case in the function definition.

The idea is to initialize parameters with some default values in case no value or undefined is passed.

```
/* ===== madhavbahl.tech/dailyjs/day21 ===== */
/* ===== Join Discord: madhavbahl.tech/discord-c2e ===== */
```



```
/* ===== */
/* ===== Daily JS - Day 21 ===== */
/* ===== */
```

### ## Example 1

**\*\*Write a function to display greeting message from a person whose details are taken in the arguments (Handle the edge case where one of the arg might be missing by displaying some generic values)\*\***

Let's see how can we solve this without default params

```
```js
// Without default params
function greet (name, age, profession) {
    if (!name || !age || !profession)
        return `Greetings, I am <anonymous>
                  I am 20 years old.
                  I am a student`;
    else
        return `Greetings, I am ${name}
                  I am ${age} years old.
                  I am a ${profession}`;
}
console.log ("With all args: \n", greet ("John", 25, "SDE"));
console.log ("Without all args: \n", greet (16, "Student"));
```

```

```
/* ===== madhavbahl.tech/dailyjs/day21 ===== */
/* ===== Join Discord: madhavbahl.tech/discord-c2e ===== */
```



```
/* ===== */
/* ===== Daily JS - Day 21 ===== */
/* ===== */
```

### ## Solution to the above problem using default params

Let's see how can we make the same function in one line using default params -

```
```js
// Using default params
function greet (name="anonymous",
                age=20,
                profession="student") {

    return `Greetings, I am ${name}
        I am ${age} years old.
        I am a ${profession}`;
}

console.log ("With all args: \n", greet ("Kepler", 22, "Student"));
console.log ("Without all args: \n", greet ());
```

```

That's it for today, see you in DailyJS tomorrow :)

```
/* ===== madhavbahl.tech/dailyjs/day21 ===== */
/* ===== Join Discord: madhavbahl.tech/discord-c2e ===== */
```



```
/* ===== */
/* ===== Daily JS - Day 21 ===== */
/* ===== */

/***
 * Default Parameters
 * Write a function to display greeting message
 * from a person whose details are taken in the arguments
 * (Handle the edge case where one of the arg might be missing
 * by displaying some generic values
 */

// Without default params
function greet (name, age, profession) {
    if (!name || !age || !profession)
        return `Greetings, I am <anonymous>
                  I am 20 years old.
                  I am a student`;
    else
        return `Greetings, I am ${name}
                  I am ${age} years old.
                  I am a ${profession}`;
}
console.log ("With all args: \n", greet ("John", 25, "SDE"));
console.log ("Without all args: \n", greet (16, "Student"));

// Using default params
function greetings (name="anonymous", age=20, profession="student") {
    return `Greetings, I am ${name}
              I am ${age} years old.
              I am a ${profession}`;
}
console.log ("With all args: \n", greetings ("Kepler", 22, "Student"));
console.log ("Without all args: \n", greetings ());

/* ===== madhavbahl.tech/dailyjs/day21 ===== */
/* ===== Join Discord: madhavbahl.tech/discord-c2e ===== */
```



# Thank you!

**Feel free to reach out...**

Email: [theleanprogrammer@gmail.com](mailto:theleanprogrammer@gmail.com)

Web: [madhavbahl.tech/](http://madhavbahl.tech/)

Github: [github.com/MadhavBahlMD](https://github.com/MadhavBahlMD)

LinkedIn: [linkedin.com/in/madhavbahl/](https://linkedin.com/in/madhavbahl/)

Insta: [instagram.com/theleanprogrammer/](https://instagram.com/theleanprogrammer/)

DAILY  
JS